



MECHANICAL GAS SAVERS

The Mechanical Gas Savers allow the operator to hang a torch from the arm, shutting off the gas and oxygen flow to the torch and therefore saving fuels when the torch is not needed. Models are available with a pilot flame on the unit so that the torch can easily be relit when needed. Depending on the model selected, Mechanical Gas Savers can be used with natural gas, propane, hydrogen, butane, methane, acetylene, or mixed gases and oxygen, air, or water.



The Mechanical Gas Savers are available in four different models. The first model is the WDW-100. The WDW-100 is used with MAPP/Propylene. The model WDW -101 is used with Acetylene. The model WDW-103 is setup to run with Natural Gas, Propane or hydrogen. **(NOTE: When using hydrogen a separate natural gas or propane feed is needed for the pilot.)** The WDW-104 is used with propane or Natural gas at 4 psi or more. All 4 models come with adjustable pilots.

CATALOG	MODEL NUMBER	Use With
28B001-0001	WDW-100	MAPP/Propylene
28B002-0001	WDW-101	Acetylene Use
28B006-0000	WDW-103	Natural Gas, Propane or Hydrogen
28B007-0000	WDW-104	Propane/Natural Gas (Above 4 PSI)

Carlisle Machine Works, Inc.,
P.O. Box 746, 412 S. Wade Blvd., Bldg. #5, Millville, NJ 08332
Phone: (856) 825- 0627 Fax: (856) 825 - 5510
Web Site: www.carlislemachine.com E-Mail: carlisle@carlislemachine.com
Toll Free In Continental US (800) 922-1167

